

INTEL® XEON® PROCESSOR PLATFORM PERFORMANCE

Hardware plus optimized software

INFERENCE THROUGHPUT



Intel® Xeon® Platinum 8180 Processor
higher Intel optimized Caffe GoogleNet v1 with Intel® MKL
inference throughput compared to
Intel® Xeon® Processor E5-2699 v3 with BVLC-Caffe

TRAINING THROUGHPUT



Intel® Xeon® Platinum 8180 Processor
higher Intel Optimized Caffe AlexNet with Intel® MKL
training throughput compared to
Intel® Xeon® Processor E5-2699 v3 with BVLC-Caffe

Inference and training throughput uses FP32 instructions



Deliver significant AI performance with hardware and software optimizations on Intel® Xeon® Scalable Family

Up to 191X Intel® Xeon® Platinum 8180 Processor higher Intel optimized Caffe Resnet50 with Intel® MKL inference throughput compared to Intel® Xeon® Processor E5-2699 v3 with BVLC-Caffe
Up to 93X Intel® Xeon® Platinum 8180 Processor higher Intel optimized Caffe Resnet50 with Intel® MKL training throughput compared to Intel® Xeon® Processor E5-2699 v3 with BVLC-Caffe

Performance estimates were obtained prior to implementation of recent software patches and firmware updates intended to address exploits referred to as "Spectre" and "Meltdown." Implementation of these updates may make these results inapplicable to your device or system.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit: <http://www.intel.com/performance>

Source: Intel measured as of June 2017. Configurations: See the last slide in this presentation. *Other names and brands may be claimed as the property of others.



CONFIGURATION DETAILS (CONT'D)

INFERENCE using FP32 Batch Size Caffe GoogleNet v1 256 AlexNet 256.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information visit <http://www.intel.com/performance> Source: Intel measured as of June 2017

Optimization Notice: Intel's compilers may or may not optimize to the same degree for non-Intel microprocessors for optimizations that are not unique to Intel microprocessors. These optimizations include SSE2, SSE3, and SSSE3 instruction sets and other optimizations. Intel does not guarantee the availability, functionality, or effectiveness of any optimization on microprocessors not manufactured by Intel. Microprocessor-dependent optimizations in this product are intended for use with Intel microprocessors. Certain optimizations not specific to Intel microarchitecture are reserved for Intel microprocessors. Please refer to the applicable product User and Reference Guides for more information regarding the specific instruction sets covered by this notice.

Configurations 40, 41:

Platform: 2S Intel® Xeon® Platinum 8180 CPU @ 2.50GHz (28 cores), HT disabled, turbo disabled, scaling governor set to "performance" via intel_pstate driver, 384GB DDR4-2666 ECC RAM. CentOS Linux release 7.3.1611 (Core), Linux kernel 3.10.0-514.10.2.el7.x86_64. SSD: Intel® SSD DC S3700 Series (800GB, 2.5in SATA 6Gb/s, 25nm, MLC). Performance measured with: Environment variables: KMP_AFFINITY=granularity=fine, compact, OMP_NUM_THREADS=56, CPU Freq set with cpupower frequency-set -d 2.5G -u 3.8G -g performance. Deep Learning Frameworks: Caffe: (<http://github.com/intel/caffe/>), revision f96b759f71b2281835f690af267158b82b150b5c. Inference measured with "caffe time --forward_only" command, training measured with "caffe time" command. For "ConvNet" topologies, dummy dataset was used. For other topologies, data was stored on local storage and cached in memory before training. Topology specs from https://github.com/intel/caffe/tree/master/models/intel_optimized_models (GoogLeNet, AlexNet, and ResNet-50), https://github.com/intel/caffe/tree/master/models/default_vgg_19 (VGG-19), and https://github.com/soumith/convnet-benchmarks/tree/master/caffe/imagenet_winners (ConvNet benchmarks; files were updated to use newer Caffe prototxt format but are functionally equivalent). Intel C++ compiler ver. 17.0.2 20170213, Intel MKL small libraries version 2018.0.20170425. Caffe run with "numactl -l".

Platform: 2S Intel® Xeon® CPU E5-2699 v3 @ 2.30GHz (18 cores), HT enabled, turbo disabled, scaling governor set to "performance" via intel_pstate driver, 256GB DDR4-2133 ECC RAM. CentOS Linux release 7.3.1611 (Core), Linux kernel 3.10.0-514.el7.x86_64. OS drive: Seagate® Enterprise ST2000NX0253 2 TB 2.5" Internal Hard Drive. Performance measured with: Environment variables: KMP_AFFINITY='granularity=fine, compact,1,0', OMP_NUM_THREADS=36, CPU Freq set with cpupower frequency-set -d 2.3G -u 2.3G -g performance. Deep Learning Frameworks: Intel Caffe: (<http://github.com/intel/caffe/>), revision b0ef3236528a2c7d2988f249d347d5fdae831236. Inference measured with "caffe time --forward_only" command, training measured with "caffe time" command. For "ConvNet" topologies, dummy dataset was used. For other topologies, data was stored on local storage and cached in memory before training. Topology specs from https://github.com/intel/caffe/tree/master/models/intel_optimized_models (GoogLeNet, AlexNet, and ResNet-50), https://github.com/intel/caffe/tree/master/models/default_vgg_19 (VGG-19), and https://github.com/soumith/convnet-benchmarks/tree/master/caffe/imagenet_winners (ConvNet benchmarks; files were updated to use newer Caffe prototxt format but are functionally equivalent). GCC 4.8.5, MKLML version 2017.0.2.20170110. BVLC-Caffe: <https://github.com/BVLC/caffe>, Inference & Training measured with "caffe time" command. For "ConvNet" topologies, dummy dataset was used. For other topologies, data was stored on local storage and cached in memory before training. BVLC Caffe (<http://github.com/BVLC/caffe/>), revision 91b09280f5233cfc62954c98ce8bc4c204e7475 (commit date 5/14/2017). BLAS: atlas ver. 3.10.1.

LEGAL NOTICES & DISCLAIMERS

This document contains information on products, services and/or processes in development. All information provided here is subject to change without notice. Contact your Intel representative to obtain the latest forecast, schedule, specifications and roadmaps.

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software or service activation. Learn more at intel.com, or from the OEM or retailer. No computer system can be absolutely secure.

Tests document performance of components on a particular test, in specific systems. Differences in hardware, software, or configuration will affect actual performance. Consult other sources of information to evaluate performance as you consider your purchase. For more complete information about performance and benchmark results, visit <http://www.intel.com/performance>.

Cost reduction scenarios described are intended as examples of how a given Intel-based product, in the specified circumstances and configurations, may affect future costs and provide cost savings. Circumstances will vary. Intel does not guarantee any costs or cost reduction.

Statements in this document that refer to Intel's plans and expectations for the quarter, the year, and the future, are forward-looking statements that involve a number of risks and uncertainties. A detailed discussion of the factors that could affect Intel's results and plans is included in Intel's SEC filings, including the annual report on Form 10-K.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Performance estimates were obtained prior to implementation of recent software patches and firmware updates intended to address exploits referred to as "Spectre" and "Meltdown." Implementation of these updates may make these results inapplicable to your device or system.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

Intel does not control or audit third-party benchmark data or the web sites referenced in this document. You should visit the referenced web site and confirm whether referenced data are accurate.

Intel, the Intel logo, Pentium, Celeron, Atom, Core, Xeon, Movidius, Saffron and others are trademarks of Intel Corporation in the U.S. and/or other countries. *Other names and brands may be claimed as the property of others.

© 2018 Intel Corporation.